

# SPEC & PRICE LIST

## MAVERICK 1010S 20inch

[2pieces]

Size	S-LoDisk 5H-114.3								Lo Disk 5H-112 5H-114.3 5H-120								Hi Disk 5H-112 5H-114.3 5H-120										
	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm							Order Inset			
20×8.0J	56(33)	50(39)	44(45)	38(51)	35(54)			56~35		48(33)	42(39)	36(45)	30(51)	27(54)			48~27			34(34)	28(40)	22(46)	16(52)				35~14
20×8.5J	56(39)	50(45)	44(51)	38(57)	32(63)	28(67)		56~28	54(33)	48(39)	42(45)	36(51)	30(57)	24(63)	20(67)		54~20		40(34)	34(40)	28(46)	22(52)	16(58)	10(64)	7(67)		41~7
20×9.0J	56(46)	50(52)	44(58)	38(64)	32(70)	26(76)	20(82)	56~20	54(40)	48(46)	42(52)	36(58)	30(64)	24(70)	18(76)	12(82)	54~12	46(35)	40(41)	34(47)	28(53)	22(59)	16(65)	10(71)	4(77)		47~-1
20×9.5J	56(52)	50(58)	44(64)	38(70)	32(76)	26(82)	20(88)	56~20	54(46)	48(52)	42(58)	36(64)	30(70)	24(76)	18(82)	12(88)	54~12	46(41)	40(47)	34(53)	28(59)	22(65)	16(71)	10(77)	4(83)	-2(89)	47~-1
20×10.0J	56(58)	50(64)	44(70)	38(76)	32(82)	26(88)		56~26	54(53)	48(59)	42(65)	36(71)	30(77)	24(83)	18(89)		54~18	46(48)	40(54)	34(60)	28(66)	22(72)	16(78)	10(84)	5(89)		47~5
20×10.5J	56(65)	50(71)	44(77)	38(83)	32(89)	26(95)		56~22	54(59)	48(65)	42(71)	36(77)	30(83)	24(89)	18(95)		54~14	46(54)	40(60)	34(66)	28(72)	22(78)	16(84)	10(90)	4(96)		47~-1

■DISK FINISH: SAMURAI GOLD、METAL SILVER、BRUSHED (21inch NORMAL RIM、20inch REVERSE RIM only)

■COMPONENT PARTS : CENTER CAP (AVAILABLE IN 5 COLORS) 、METAL VALVE STEM、LONG SOCKET ADAPTOR

■RIM DEPTH:THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※SAME PRICES ON YOUR CUSTOM ORDER.

WARNING : THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE.  
(OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)		
	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi
21 Normal	—	—	—	—	φ66.5	705KG	φ29	φ15	φ73	690KG	φ30	φ13	φ72.5	690KG	φ29	φ15	27	35	48
20	—	—	—	—															
20 Normal	φ65	540KG	φ29	φ15															
19																			
19 Normal					—	—	—	—											
18	—	—	—	—															