

SPEC & PRICE LIST

MAVERICK 905S 18inch REVERSE RIM

[2pieces]

| Price Size (Tax excluding/1pc) | BLACK/ POLISH | GUN-META/ POLISH | MAT BLACK | S-Lo Disk 5H-114.3 | | | | | | | | Lo Disk 5H-100 5H-114.3 | | | | | | | | |
|-----------------------------------|------------------|---------------------|--------------|--------------------|----------------------|--------|--------|--------|--------|--------|--------|-------------------------|----------------------|--------|--------|--------|--------|--------|--------|--------|
| | | | | Order Inset | Inset (Rim Depth) mm | | | | | | | Order Inset | Inset (Rim Depth) mm | | | | | | | |
| 18×7.5J | ¥61,000 | ¥61,000 | ¥60,000 | 49~31 | | 49(35) | 44(40) | 38(46) | 32(52) | | | 41~23 | | | 41(34) | 36(39) | 30(45) | 24(51) | | |
| 18×8.0J | ¥62,000 | ¥62,000 | ¥61,000 | 55~25 | 55(35) | 50(40) | 44(46) | 38(52) | 32(58) | 26(64) | | 47~17 | | 47(34) | 42(39) | 36(45) | 30(51) | 24(57) | 18(63) | |
| 18×8.5J | ¥63,000 | ¥63,000 | ¥62,000 | 56~18 | 56(40) | 50(46) | 44(52) | 38(58) | 32(64) | 26(70) | 20(76) | 53~10 | 53(34) | 48(39) | 42(45) | 36(51) | 30(57) | 24(63) | 18(69) | 12(75) |
| 18×9.0J | ¥64,000 | ¥64,000 | ¥63,000 | 56~19 | 56(47) | 50(53) | 44(59) | 38(65) | 32(71) | 26(77) | 20(83) | 54~11 | 54(40) | 48(46) | 42(52) | 36(58) | 30(64) | 24(70) | 18(76) | 12(82) |
| 18×9.5J | ¥65,000 | ¥65,000 | ¥64,000 | 56~18 | 56(53) | 50(59) | 44(65) | 38(71) | 32(77) | 26(83) | 20(89) | 54~10 | 54(46) | 48(52) | 42(58) | 36(64) | 30(70) | 24(76) | 18(82) | 12(88) |
| 18×10.0J | ¥66,000 | ¥66,000 | ¥65,000 | 56~25 | 56(60) | 50(66) | 44(72) | 38(78) | 32(84) | 26(90) | | 54~17 | 54(53) | 48(59) | 42(65) | 36(71) | 30(77) | 24(83) | 18(89) | |

WARNING : THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE.

(OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

■DISK FINISH: GUN-META/POLISH, BLACK/POLISH, MAT BLACK

■COMPONENT PARTS : CENTER CAP (Two colors for Hi type and five colors for Lo type are available.)、METAL VALVE STEM, LONG SOCKET ADAPTOR

■RIM DEPTH:THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※SAME PRICES ON YOUR CUSTOM ORDER.

| Size | 5H/100 | | | | 5H/112 | | | | 5H/114.3 | | | | 5H/120 | | | | Height of hub clearance (mm) | | | | | | | | | |
|------------|--------|-------|--------------|---------------|--------|-------|--------------|---------------|----------|-------|--------------|---------------|--------|-------|--------------|---------------|------------------------------|----|----|---|---|---|---|---|---|---|
| | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | S-Lo | Lo | Hi | | | | | | | |
| 21 Normal | — | — | — | — | φ66.5 | 705KG | φ28.5 | φ15 | φ73 | 690KG | φ30 | φ13 | φ72.5 | 690KG | φ28.5 | φ15 | 26 | 35 | 48 | | | | | | | |
| 20 Reverse | — | — | — | — | | | | | | | | | — | — | — | — | | | | — | — | — | — | — | — | — |
| 20 Normal | — | — | — | — | — | — | — | — | | | | | — | — | — | — | | | | — | — | — | — | — | — | — |
| 19 Reverse | φ65 | 540KG | φ28.5 | φ15 | φ66.5 | 700KG | φ28.5 | φ15 | | | | | — | — | — | — | | | | — | — | — | — | — | — | — |
| 18 Reverse | — | — | — | — | — | — | — | — | — | — | — | — | — | — | — | — | — | — | — | | | | | | | |