

# SPEC & PRICE LIST

## MAVERICK 905S 20inch REVERSE RIM

[2pieces]

Price Size (Tax excluding/1pc)	BLACK/ POLISH	GUN-META/ POLISH	MAT BLACK	S-Lo Disk 5H-114.3								Lo Disk 5H-112 5H-114.3 5H-120								Hi Disk 5H-112 5H-114.3 5H-120										
				Order Inset		Inset (Rim Depth) mm						Order Inset		Inset (Rim Depth) mm						Order Inset		Inset (Rim Depth) mm								
				56~34	56(34)	50(40)	44(43)	38(52)	34(56)			47~25		47(34)	42(39)	36(45)	30(51)	25(56)			34~12		33(35)	28(40)	22(46)	16(52)	12(56)			
20×8.0J	¥82,000	¥82,000	¥81,000	56~34	56(34)	50(40)	44(43)	38(52)	34(56)			47~25		47(34)	42(39)	36(45)	30(51)	25(56)			34~12		33(35)	28(40)	22(46)	16(52)	12(56)			
20×8.5J	¥83,000	¥83,000	¥82,000	56~27	56(41)	50(47)	44(53)	38(59)	32(65)	27(70)		53~18	53(35)	48(40)	42(46)	36(52)	30(58)	24(64)	18(70)		40~5		40(35)	34(41)	28(47)	22(53)	16(59)	10(65)	5(69)	
20×9.0J	¥84,000	¥84,000	¥83,000	56~20	56(47)	50(53)	44(59)	38(65)	32(71)	26(77)	20(83)	54~11	54(40)	48(46)	42(52)	36(58)	30(64)	24(70)	18(76)	12(82)	46~-2	46(35)	40(41)	34(47)	28(53)	22(59)	16(65)	10(71)	4(77)	-2(83)
20×9.5J	¥85,000	¥85,000	¥84,000	56~19	56(54)	50(60)	44(66)	38(72)	32(78)	26(84)	20(90)	54~10	54(47)	48(53)	42(59)	36(65)	30(71)	24(77)	18(83)	12(89)	46~-3	46(42)	40(48)	34(54)	28(60)	22(66)	16(72)	10(78)	4(84)	-2(90)
20×10.0J	¥86,000	¥86,000	¥85,000	56~26	56(60)	50(66)	44(72)	38(78)	32(84)	26(90)		54~17	54(53)	48(59)	42(65)	36(71)	30(77)	24(83)	18(89)		46~4	46(48)	40(54)	34(60)	28(66)	22(72)	16(78)	10(84)	4(90)	
20×10.5J	¥87,000	¥87,000	¥86,000	56~22	56(66)	50(72)	44(78)	38(84)	32(90)	26(96)		54~13	54(59)	48(65)	42(71)	36(77)	30(83)	24(89)	18(95)	13(100)	46~0	46(54)	40(60)	34(66)	28(72)	22(78)	16(84)	10(90)	4(96)	

WARNING : THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE.

(OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

■DISK FINISH: GUN-META/POLISH, BLACK/POLISH, MAT BLACK

■COMPONENT PARTS : CENTER CAP (Two colors for Hi type and five colors for Lo type are available.)、METAL VALVE STEM, LONG SOCKET ADAPTOR

■RIM DEPTH:THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)									
	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi							
21 Normal	—	—	—	—	φ66.5	705KG	φ28.5	φ15	φ73	690KG	φ30	φ13	φ72.5	690KG	φ28.5	φ15	26	35	48							
20 Reverse	—	—	—	—									—	—	—	—				—	—	—	—	—	—	—
20 Normal	—	—	—	—	—	—	—	—					—	—	—	—				—	—	—	—	—	—	—
19 Reverse	φ65	540KG	φ28.5	φ15	φ66.5	700KG	φ28.5	φ15					—	—	—	—				—	—	—	—	—	—	—
18 Reverse	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—							