

# SPEC & PRICE LIST

## MAVERICK 905S 20inch NORMAL RIM

[2pieces]

Price Size (Tax excluding/1pc)	BLACK/ POLISH	GUN-META/ POLISH	MAT BLACK	S-Lo Disk 5H-114.3										Lo Disk 5H-100 5H-114.3										Hi Disk 5H-114.3																		
				Order Inset		Inset (Rim Depth) mm								Order Inset		Inset (Rim Depth) mm								Order Inset		Inset (Rim Depth) mm																
				20×8.5J	¥83,000	¥83,000	¥82,000	38~20			38(59)	35(62)	29(68)	23(74)					31~13				31(57)	27(61)	21(67)	15(73)					18~0					18(57)	13(62)	7(68)	1(74)			
20×9.0J	¥84,000	¥84,000	¥83,000	45~14		45(59)	41(63)	35(69)	29(75)	23(81)	17(87)			38~7				38(57)	33(62)	27(68)	21(74)	15(80)	9(86)			25~6					25(57)	19(63)	13(69)	7(75)	1(81)	-5(87)						
20×9.5J	¥85,000	¥85,000	¥84,000	51~8	51(59)	47(63)	41(69)	35(75)	29(81)	23(87)	17(93)	11(99)		44~1		44(57)	39(62)	33(68)	27(74)	21(80)	15(86)	9(92)	3(98)			31~13				31(57)	25(63)	19(69)	13(75)	7(81)	1(87)	-5(93)	-11(99)					
20×10.0J	¥86,000	¥86,000	¥85,000	53~2	53(63)	47(69)	41(75)	35(81)	29(87)	23(93)	17(99)	11(105)	5(111)	51~5	51(56)	45(62)	39(68)	33(74)	27(80)	21(86)	15(92)	9(98)	3(104)			38~18			37(57)	31(63)	25(69)	19(75)	13(81)	7(87)	1(93)	-5(99)	-11(105)	-17(111)				
20×10.5J	¥87,000	¥87,000	¥86,000	53~8	53(70)	47(76)	41(82)	35(88)	29(94)	23(100)	17(106)	11(112)		51~1	51(63)	45(69)	39(75)	33(81)	27(87)	21(93)	15(99)	9(105)	3(111)			44~12	43(58)	37(64)	31(70)	25(76)	19(82)	13(88)	7(94)	1(100)	-5(106)	-11(112)						
20×11.0J	¥88,000	¥88,000	¥87,000	53~8	53(76)	47(82)	41(88)	35(94)	29(100)	23(106)	17(112)	11(118)		51~1	51(69)	45(75)	39(81)	33(87)	27(93)	21(99)	15(105)	9(111)	3(117)			44~13	43(64)	37(70)	31(76)	25(82)	19(88)	13(94)	7(100)	1(106)	-5(112)	-11(118)						

WARNING : THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE.

(OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

■DISK FINISH: GUN-META/POLISH, BLACK/POLISH, MAT BLACK

■COMPONENT PARTS : CENTER CAP (Two colors for Hi type and five colors for Lo type are available.)、METAL VALVE STEM, LONG SOCKET ADAPTOR

■RIM DEPTH:THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)													
	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi											
21 Normal	—	—	—	—	φ66.5	705KG	φ28.5	φ15	φ73	690KG	φ30	φ13	φ72.5	690KG	φ28.5	φ15	26	35	48											
20 Reverse	—	—	—	—									—	—	—	—				—	—	—	—	—	—	—	—	—	—	
20 Normal	—	—	—	—									—	—	—	—				—	—	—	—	—	—	—	—	—	—	—
19 Reverse	φ65	540KG	φ28.5	φ15									φ66.5	700KG	φ28.5	φ15				—	—	—	—	—	—	—	—	—	—	—
18 Reverse	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—											