

SPEC & PRICE LIST

MAVERICK 1505S 21inch NORMAL RIM

[2pieces]

| Size | Price (JPY/1pc) | | S-Lo Disk 5H-114.3 5H-120 | | | | | | Lo Disk 5H-112 5H-114.3 5H-120 | | | | | | Hi Disk 5H-112 5H-114.3 5H-120 | | | | | | | | | | |
|----------|-------------------|---------------------------|---------------------------|----------------------|--------|---------|---------|---------|--------------------------------|-------------|----------------------|--------|--------|---------|--------------------------------|---------|-------------|----------------------|--------|--------|--------|---------|---------|--------|---------|
| | HYPER METAL BLACK | SAMURAI GOLD, WHITE (BTO) | Order Inset | Inset (Rim Depth) mm | | | | | | Order Inset | Inset (Rim Depth) mm | | | | | | Order Inset | Inset (Rim Depth) mm | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| 21×9.0J | ¥107,000 | ¥103,000 | 35~21 | | | 35(76) | 29(82) | 23(88) | | 23~9 | | | | 23(76) | 17(82) | 11(88) | | 18~4 | | | | 17(77) | 11(83) | 5(89) | |
| 21×9.5J | ¥108,000 | ¥104,000 | 41~15 | | 41(77) | 35(83) | 29(89) | 23(95) | 17(101) | 31~3 | | | 29(77) | 23(83) | 17(89) | 11(95) | 5(101) | 24~2 | | | 23(78) | 17(84) | 11(90) | 5(96) | -1(102) |
| 21×10.0J | ¥109,000 | ¥105,000 | 47~15 | 47(77) | 41(83) | 35(89) | 29(95) | 23(101) | 17(107) | 37~3 | | 35(77) | 29(83) | 23(89) | 17(95) | 11(101) | 5(107) | 30~2 | | 29(78) | 23(84) | 17(90) | 11(96) | 5(102) | -1(108) |
| 21×10.5J | ¥110,000 | ¥106,000 | 47~21 | 47(83) | 41(89) | 35(95) | 29(101) | 23(107) | | 43~9 | 41(77) | 35(83) | 29(89) | 23(95) | 17(101) | 11(107) | | 36~4 | 35(78) | 29(84) | 23(90) | 17(96) | 11(102) | 5(108) | |
| 21×11.0J | ¥111,000 | ¥107,000 | 47~22 | 47(90) | 41(96) | 35(102) | 29(108) | 23(114) | | 43~10 | 41(84) | 35(90) | 29(96) | 23(102) | 17(108) | 11(114) | | 36~5 | 35(85) | 29(91) | 23(97) | 17(103) | 11(109) | 5(115) | |

■DISK FINISH: Hyper Metal Black, Samurai Gold, White (build to order)

■COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type),AIR VALVE

*As of November 30, 2023, the long adapter is no longer included.

■RIM DEPTH : THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

*SAME PRICES ON YOUR CUSTOM ORDER.

| Size | 5H/100 | | | | 5H/112 | | | | 5H/114.3 | | | | 5H/120 | | | | Height of hub clearance (mm) | | | |
|------------|--------|-------|--------------|---------------|--------|-------|--------------|---------------|----------|-------|--------------|---------------|--------|-------|--------------|---------------|------------------------------|------|----|----|
| | HUBφ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUBφ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUBφ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUBφ | VIA | LUG HOLE DIA | BOLT HOLE DIA | EX-Lo | S-Lo | Lo | Hi |
| 21 Normal | — | — | — | — | φ66.5 | 705KG | φ30 | φ14.5 | φ73 | 690KG | φ30 | φ14.5 | φ72.5 | 690KG | φ30 | φ14.5 | — | 28 | 40 | 45 |
| 20 Reverse | — | — | — | — | | | | | | | | | | | | | 23 | | | |
| 19 Reverse | φ65 | 540KG | φ30 | φ14.5 | | — | | | | | | | | | | | | | | |
| 18 Reverse | | | | | | — | | | | | | | | | | | | | | |

SPEC & PRICE LIST

MAVERICK 1505S 20inch REVERSE RIM

[2pieces]

| Size | Price (JPY/1pc) | | CONCAVE FACE | | | | | | | | | | | | REGULAR FACE | | | | | | | | | | | | | | | | | | | | | |
|----------|-------------------|---------------------------|----------------------------|----------------------|--------|--------|---------------------------|----------------------|--------|--------|--------------------------------|----------------------|--------|--------|--------------------------------|----------------------|--------|--------|--------|--------|--------|--------|--------|---------|---------|-------|--------|--------|--------|--------|--------|--------|--------|--------|-------|-------|
| | HYPER METAL BLACK | SAMURAI GOLD, WHITE (BTO) | EX-Lo Disc 5H-114.3 5H-120 | | | | S-Lo Disk 5H-114.3 5H-120 | | | | Lo Disk 5H-112 5H-114.3 5H-120 | | | | Hi Disk 5H-112 5H-114.3 5H-120 | | | | | | | | | | | | | | | | | | | | | |
| | | | Order Inset | Inset (Rim Depth) mm | | | Order Inset | Inset (Rim Depth) mm | | | Order Inset | Inset (Rim Depth) mm | | | Order Inset | Inset (Rim Depth) mm | | | | | | | | | | | | | | | | | | | | |
| 20×8.5J | ¥94,000 | ¥90,000 | 35~33 | | | 33(77) | | | 50~28 | | 50(55) | 44(61) | 38(67) | 32(73) | 28(77) | | 38~16 | | | 38(55) | 32(61) | 26(67) | 20(73) | 16(77) | | 33~11 | | | 32(56) | 26(62) | 20(68) | 14(74) | 11(77) | | | |
| 20×9.0J | ¥95,000 | ¥91,000 | 41~25 | | | 39(77) | 33(83) | 27(89) | 56~20 | 56(55) | 50(61) | 44(67) | 38(73) | 32(79) | 26(85) | | 44~8 | | | 44(55) | 38(61) | 32(67) | 26(73) | 20(79) | 14(85) | 8(91) | 39~3 | | | 38(56) | 32(62) | 26(68) | 20(74) | 14(80) | 8(86) | 3(91) |
| 20×9.5J | ¥96,000 | ¥92,000 | 48~25 | | | 45(78) | 39(84) | 33(90) | 27(96) | 56~20 | 56(62) | 50(68) | 44(74) | 38(80) | 32(86) | 26(92) | 20(91) | 50~8 | 50(56) | 44(62) | 38(68) | 32(74) | 26(80) | 20(86) | 14(92) | 8(98) | 45~3 | 44(56) | 38(62) | 32(68) | 26(74) | 20(80) | 14(86) | 8(92) | 3(97) | |
| 20×10.0J | ¥97,000 | ¥93,000 | 54~31 | 51(78) | 45(84) | 39(90) | 33(96) | | 56~26 | 56(68) | 50(74) | 44(80) | 38(86) | 32(92) | 26(98) | 20(98) | 50~14 | 50(62) | 44(68) | 38(74) | 32(80) | 26(86) | 20(92) | 14(98) | | 48~9 | 44(63) | 38(69) | 32(75) | 26(81) | 20(87) | 14(93) | 9(98) | | | |
| 20×10.5J | ¥98,000 | ¥94,000 | 54~27 | 51(84) | 45(90) | 39(96) | 33(102) | 27(108) | 56~22 | 56(74) | 50(80) | 44(86) | 38(92) | 32(98) | 26(104) | | 50~10 | 50(68) | 44(74) | 38(80) | 32(86) | 26(92) | 20(98) | 14(104) | 10(108) | 48~5 | 44(69) | 38(75) | 32(81) | 26(87) | 20(93) | 14(99) | 8(105) | | | |

**WARNING : FOR EX-LO DISCS, THE TOP SURFACE OF THE DISC PROTRUDES FROM THE RIM FLANGE END FACE WHEN THE OUTER RIM DEPTH IS 76mm OR LESS.
FOR S-LO TO HI DISCS, THE TOP SURFACE OF THE DISC PROTRUDES FROM THE RIM FLANGE END SURFACE WHEN THE OUTER RIM DEPTH IS 57mm OR LESS.**

- DISK FINISH: Hyper Metal Black, Samurai Gold, White (built to order)
- COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH : THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- *SAME PRICES ON YOUR CUSTOM ORDER.

| Size | 5H/100 | | | | 5H/112 | | | | 5H/114.3 | | | | 5H/120 | | | | Height of hub clearance (mm) | | | |
|------------|--------|-------|--------------|---------------|--------|-------|--------------|---------------|----------|-------|--------------|---------------|--------|-------|--------------|---------------|------------------------------|------|----|----|
| | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | EX-Lo | S-Lo | Lo | Hi |
| 21 Normal | — | — | — | — | φ66.5 | 705KG | φ30 | φ14.5 | φ73 | 690KG | φ30 | φ14.5 | φ72.5 | 690KG | φ30 | φ14.5 | — | 28 | 40 | 45 |
| 20 Reverse | — | — | — | — | | | | | | | | | | | | | | | | |
| 19 Reverse | φ65 | 540KG | φ30 | φ14.5 | | | | | | | | | | | | | — | | | |
| 18 Reverse | — | — | — | — | | | | | | | | | | | | | — | | | |

SPEC & PRICE LIST

MAVERICK 1505S 19inch REVERSE RIM

[2pieces]

| Size | Price (JPY/1pc) | | S-Lo Disk 5H-114.3 | | | | | | | | Lo Disk 5H-100 5H-112 5H-114.3 5H-120 | | | | | | | | Hi Disk 5H-114.3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------|-------------------|---------------------------|--------------------|----------------------|--------|--------|--------|--------|---------|--------|---------------------------------------|-------------|----------------------|--|--|--|--|-------|------------------|--------|-------------|----------------------|--------|--------|---------|-------|--|--|--------|--------|--------|--------|--------|--|------|--------|--------|--------|--------|--------|--------|--------|-------|--|--|--------|--------|--------|--------|--------|--|--|--|--|
| | HYPER METAL BLACK | SAMURAI GOLD, WHITE (BTO) | Order Inset | Inset (Rim Depth) mm | | | | | | | | Order Inset | Inset (Rim Depth) mm | | | | | | | | Order Inset | Inset (Rim Depth) mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 19×7.5J | ¥80,000 | ¥76,000 | 43~40 | | | | | | | | 43(49) | | | | | | | | 31~28 | | | | | | | | | | | 31(49) | | | | | | | | 26~23 | | | | | | | | | 26(50) | | | | | | | |
| 19×8.0J | ¥81,000 | ¥77,000 | 50~35 | | | | | | | | 50(49) | 44(55) | 38(61) | | | | | | 38~23 | | | | | | | | | | | 38(49) | 32(55) | 26(61) | | | | | | 33~18 | | | | | | | | | 32(50) | 26(56) | 20(62) | | | | | |
| 19×8.5J | ¥82,000 | ¥78,000 | 56~28 | 56(49) | 50(55) | 44(61) | 38(67) | 32(73) | | | | | | | | | | 44~16 | | | | | | | | | | | 44(49) | 38(55) | 32(61) | 26(67) | 20(73) | | | | 39~11 | | | | | | | | | 38(50) | 32(56) | 26(62) | 20(68) | 14(74) | | | | |
| 19×9.0J | ¥83,000 | ¥79,000 | 56~20 | 56(55) | 50(61) | 44(67) | 38(73) | 32(79) | 26(85) | 20(91) | | | | | | | | 50~8 | 50(49) | 44(55) | 38(61) | 32(67) | 26(73) | 20(79) | 14(85) | 8(91) | | | | | | | | | | 45~3 | 44(50) | 38(56) | 32(62) | 26(68) | 20(74) | 14(80) | 8(86) | | | | | | | | | | | |
| 19×9.5J | ¥84,000 | ¥80,000 | 56~20 | 56(62) | 50(68) | 44(74) | 38(80) | 32(86) | 26(92) | 20(98) | | | | | | | | 50~8 | 50(56) | 44(62) | 38(68) | 32(74) | 26(80) | 20(86) | 14(92) | 8(98) | | | | | | | | | | 48~3 | 44(57) | 38(63) | 32(69) | 26(75) | 20(81) | 14(87) | 8(93) | | | | | | | | | | | |
| 19×10.0J | ¥85,000 | ¥81,000 | 56~26 | 56(68) | 50(74) | 44(80) | 38(86) | 32(92) | 26(98) | | | | | | | | | 50~14 | 50(62) | 44(68) | 38(74) | 32(80) | 26(86) | 20(92) | 14(98) | | | | | | | | | | 48~9 | 44(63) | 38(69) | 32(75) | 26(81) | 20(87) | 14(93) | | | | | | | | | | | | | |
| 19×10.5J | ¥86,000 | ¥82,000 | 56~22 | 56(74) | 50(80) | 44(86) | 38(92) | 32(98) | 26(104) | | | | | | | | | 50~10 | 50(68) | 44(74) | 38(80) | 32(86) | 26(92) | 20(98) | 14(104) | | | | | | | | | | 48~5 | 44(69) | 38(75) | 32(81) | 26(87) | 20(93) | 14(99) | | | | | | | | | | | | | |

NOTE: FOR OUTER RIM DEPTHS OF 52mm OR LESS, THE TOP SURFACE OF THE DISC PROTRUDES FROM THE EDGE OF THE RIM FLANGE.
 (When the outer rim depth is 49mm, 3.3mm protrudes.)

- DISK FINISH: Hyper Metal Black, Samurai Gold, White (build to order)
- COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH : THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- *SAME PRICES ON YOUR CUSTOM ORDER.

| Size | 5H/100 | | | | 5H/112 | | | | 5H/114.3 | | | | 5H/120 | | | | Height of hub clearance (mm) | | | |
|------------|--------|-------|--------------|---------------|--------|-------|--------------|---------------|----------|-------|--------------|---------------|--------|-------|--------------|---------------|------------------------------|------|----|----|
| | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | EX-Lo | S-Lo | Lo | Hi |
| 21 Normal | — | — | — | — | φ 66.5 | 705KG | φ 30 | φ 14.5 | φ 73 | 690KG | φ 30 | φ 14.5 | φ 72.5 | 690KG | φ 30 | φ 14.5 | — | 28 | 40 | 45 |
| 20 Reverse | — | — | — | — | | | | | | | | | | | | | | | | |
| 19 Reverse | — | — | — | — | | | | | | | | | | | | | | | | |
| 18 Reverse | φ 65 | 540KG | φ 30 | φ 14.5 | | 700KG | | | | | | | — | — | — | — | | | | |

SPEC & PRICE LIST

MAVERICK 1505S 18inch REVERSE RIM

[2pieces]

| Size | Price (JPY/1pc) | | S-Lo Disk 5H-114.3 | | | | | | | Lo Disk 5H-100 5H-112 5H-114.3 | | | | | | | | | |
|----------|-------------------|---------------------------|--------------------|----------------------|--------|--------|--------|--------|--------|--------------------------------|-------------|----------------------|--------|--------|--------|--------|--------|--------|-------|
| | HYPER METAL BLACK | SAMURAI GOLD, WHITE (BTO) | Order Inset | Inset (Rim Depth) mm | | | | | | | Order Inset | Inset (Rim Depth) mm | | | | | | | |
| | | | | | | | | | | | | | | | | | | | |
| 18×7.5J | ¥74,000 | ¥70,000 | 43~32 | | 43(49) | 38(55) | 32(61) | | | 31~20 | | | | 31(49) | 26(54) | 20(60) | | | |
| 18×8.0J | ¥75,000 | ¥71,000 | 50~27 | 50(49) | 44(55) | 38(61) | 32(67) | 27(72) | | 38~15 | | | 38(49) | 32(55) | 26(61) | 20(67) | 15(72) | | |
| 18×8.5J | ¥76,000 | ¥72,000 | 50~20 | 50(55) | 44(61) | 38(67) | 32(73) | 26(79) | 20(85) | 44~8 | | | 44(49) | 38(55) | 32(61) | 26(67) | 20(73) | 14(79) | 8(85) |
| 18×9.0J | ¥77,000 | ¥73,000 | 50~20 | 50(61) | 44(67) | 38(73) | 32(79) | 26(85) | 20(91) | 50~8 | 50(49) | 44(55) | 38(61) | 32(67) | 26(73) | 20(79) | 14(85) | 8(91) | |
| 18×9.5J | ¥78,000 | ¥74,000 | 50~20 | 50(68) | 44(74) | 38(80) | 32(86) | 26(92) | 20(98) | 50~8 | 50(56) | 44(62) | 38(68) | 32(74) | 26(80) | 20(86) | 14(92) | 8(98) | |
| 18×10.0J | ¥79,000 | ¥75,000 | 50~26 | 50(74) | 44(80) | 38(86) | 32(92) | 26(98) | | 50~14 | 50(62) | 44(68) | 38(74) | 32(80) | 26(86) | 20(92) | 14(98) | | |

NOTE: FOR OUTER RIM DEPTHS OF 52mm OR LESS, THE TOP SURFACE OF THE DISC PROTRUDES FROM THE EDGE OF THE RIM FLANGE.
 (When the outer rim depth is 49mm, 3.3mm protrudes.)

- DISK FINISH: Hyper Metal Black, Samurai Gold, White (build to order)
- COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH : THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- *SAME PRICES ON YOUR CUSTOM ORDER.

| Size | 5H/100 | | | | 5H/112 | | | | 5H/114.3 | | | | 5H/120 | | | | Height of hub clearance (mm) | | | |
|------------|--------|-------|--------------|---------------|--------|-------|--------------|---------------|----------|-------|--------------|---------------|--------|-------|--------------|---------------|------------------------------|------|----|----|
| | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | HUB φ | VIA | LUG HOLE DIA | BOLT HOLE DIA | EX-Lo | S-Lo | Lo | Hi |
| 21 Normal | — | — | — | — | φ66.5 | 705KG | φ30 | φ14.5 | φ73 | 690KG | φ30 | φ14.5 | φ72.5 | 690KG | φ30 | φ14.5 | — | 28 | 40 | 45 |
| 20 Reverse | — | — | — | — | | | | | | | | | | | | | | | | |
| 19 Reverse | φ65 | 540KG | φ30 | φ14.5 | | | | | | | | | | | | | — | | | |
| 18 Reverse | — | — | — | — | | | | | | | | | | | | | — | | | |