

SPEC & PRICE LIST

KEELER TACTICS

[1piece]

	SIZE	INSET	H-P.C.D.	Disk Hub DIA	Bolt Hole DIA	Cap	Supported Standards	(Code) Price	
								HYPER SILVER	GLOSS BLACK
15	15×5.5J	42	6-139.7	φ110.5	φ13	Optional (WRV CAP)	JWL/JWL-T	[39704] ¥20,500	[39721] ¥21,500
	15×6.0J	0	5-139.7	φ110.5	φ13	Optional (WRV CAP)	JWL/JWL-T	[39705] ¥21,500	[39722] ¥22,500
	15×6.0J	33	6-139.7	φ110.5	φ13	Optional (WRV CAP)	JWL/JWL-T	[39706] ¥21,500	[39723] ¥22,500
16	16×5.5J	22	5-139.7	φ110.5	φ13	Optional (WRV CAP)	JWL/JWL-T	[39707] ¥24,000	[39724] ¥25,000
	16×6.5J	38	6-139.7	φ110.5	φ13	Optional (WRV CAP)	JWL/JWL-T	[39708] ¥25,000	[39725] ¥26,000
	16×7.0J	5	6-139.7	φ110.5	φ13	Optional (WRV CAP)	JWL/JWL-T	[39709] ¥25,500	[39726] ¥26,500
	16×7.0J	26	6-139.7	φ110.5	φ13	Optional (WRV CAP)	JWL/JWL-T	[39710] ¥25,500	[39727] ¥26,500
	16×7.0J ※1	38	5-114.3	φ73	φ15	ATTACHED(S)	JWL	[39711] ¥28,000	[39728] ¥29,000
17	17×7.0J	35	5-110	φ65	φ13	ATTACHED(S)	JWL	[39712] ¥33,500	[39729] ¥34,500
	17×7.0J ※1	38	5-114.3	φ73	φ15	ATTACHED(S)	JWL	[39713] ¥33,500	[39730] ¥34,500
	17×7.0J ※2	50	6-130	φ75	—	ATTACHED(L)	JWL	[39714] ¥33,500	[39731] ¥34,500
	17×7.5J ※3,4	38	5-127	φ73	φ15	ATTACHED(L)	JWL	[39715] ¥34,000	[39732] ¥35,000
	17×7.5J	40	6-139.7	φ106	φ13	ATTACHED(L)	JWL/JWL-T	[39716] ¥34,000	[39733] ¥35,000
	17×8.0J	25	6-139.7	φ106	φ13	ATTACHED(L)	JWL/JWL-T	[39717] ¥34,500	[39734] ¥35,500
	18×7.5J ★	46	6-139.7	φ67	φ15	ATTACHED(L)	JWL	[42112] ¥38,500	[42113] ¥39,500
18	18×7.5J ※2	55	6-139.7	φ95	—	ATTACHED(L)	JWL	[40447] ¥38,500	[40448] ¥39,500
	18×8.0J	25	6-139.7	φ106	φ13	ATTACHED(L)	JWL/JWL-T	[39718] ¥39,000	[39735] ¥40,000
	18×8.0J ※3,4	50	5-127	φ71.6	φ15	ATTACHED(L)	JWL	[39719] ¥39,000	[39736] ¥40,000
	18×8.0J ※2	52	5-150	φ110.1	—	ATTACHED(L)	JWL	[39720] ¥39,000	[39737] ¥40,000

★Additional size

■DISK FINISH:HYPER SILVER、GLOSS BLACK

■Accessories: Rubber valve (dedicated metal valve for 15x5.5J 42/15x6.0J 33), center cap (some sizes)

■Nut hole diameter: φ32 (*φ29 for 5H-110, φ38 for 6H-130/5H-150/18x7.5J 55)

※1:Compatible with 1/2 nut M14 bolts For vehicles with M12 hub bolts, please use hub collar rings.

※2:Compatible with genuine straight nuts

※3:Washerless processing

※4:Compatible with M14 bolts